



CPC200 (CP4000)

Aluminum Clad-Wood • Casement/Awning Picture • Pocket Insert Replacement Frame

PRODUCT SPECIFICATIONS

FRAME

- Exterior parts are of kiln dried ponderosa pine, treated with a water repellent preservative to protect from rot and insects. Also available in sapele, oak and cherry.
- Head, jamb and sill wood parts are fitted to the extruded aluminum and are of kiln dried ponderosa pine, treated with a water repellent preservative to protect from rot and insects. Also available in sapele, oak and cherry.
- Head and jamb wood joints are tenoned, glued and nailed.
- Frame thickness of 1 $\frac{5}{16}$ " at head, jamb and sill.
- Standard jamb depth: 3 $\frac{1}{4}$ " stepped jamb for sash pocket installation.
- Available with optional $\frac{3}{8}$ " foam wrap for air tight installation.
- A continuous sill (up to 120") is used on mullied units.

SASH

- Exterior parts are of kiln dried ponderosa pine, treated with a water repellent preservative to protect from rot and insects. Also available in sapele, oak and cherry.
- Sash parts are fitted to the extruded aluminum and are of kiln dried ponderosa pine, treated with a water repellent preservative to protect from rot and insects. Also available in sapele, oak and cherry.
- Sash joints are tenoned, glued and nailed from the interior.
- Silicone glazed from the interior for a positive water tight seal.
- Overall finish sash thickness: 1 $\frac{3}{4}$ ". Sash profile dimension is 2".

EXTERIOR FINISH

- Standard color options are: White, Bronze, Earthtone, Beige, Black and Hunter Green and meet the physical test requirements of AAMA 2603. Custom colors available.
- Optional AAMA 2605 finish available.

INTERIOR FINISH

- Standard in unfinished natural wood in specified species (pine (standard), sapele, oak and cherry) which can be painted or stained.
- Available factory primed or prefinished white in pine (standard), sapele, oak and cherry. Contact Trimline dealer for custom color details.

WEATHERSTRIPPING

- Unit is weather sealed with Q-Lon® almond color foam compression seal weatherstripping.

GLASS

- Standard clear $\frac{3}{4}$ " thick insulating glass, consisting of "double strength" $\frac{1}{8}$ " (3 mm) annealed glass, $\frac{1}{2}$ " air space using Tremco's EnerEDGE® warm-edge, dual-seal silicone foam spacer (dark charcoal), hermetically sealed with hot melt butyl.
- Glass also available in these thicknesses: $\frac{5}{32}$ " (3.9 mm) with $\frac{7}{16}$ " air space, $\frac{3}{16}$ " (4.7 mm) with $\frac{3}{8}$ " air space and $\frac{7}{32}$ " (5.7 mm) with $\frac{5}{16}$ " air space.
- Other glazing options include CARDINAL LoE²-270 and with obscure, tempered, laminated, bronze or grey tint. Decorative glass also available. CARDINAL LoE²-270 + LoE-i89 is available only in annealed and tempered.

GRILLES

- Optional faux check rail of .050" thick extruded aluminum in a classic putty glazed 1 ½" profile permanently applied to the exterior of the insulated glass. Double faced tape is used to apply faux check rail to the glass which first is prepared with a saline type glass bonding and coupling agent before faux check rail is applied to help ensure lasting adhesion. A dark anodized bronze shadow bar is included between the glass for an authentic check rail look. Interior wood in pine (standard), sapele, oak and cherry matching the interior wood species.
- Simulated Divided Lites (SDL) of .050" thick extruded aluminum in a classic putty glazed ⅝", ⅞", 1 ¼" or 1 ½" muntin profile permanently applied to exterior of the insulated glass. Double faced tape is used to apply muntin to the glass which first is prepared with a saline type glass bonding and coupling agent before muntin is applied to help ensure lasting adhesion. An optional between the glass dark anodized bronze shadow bar is available for an authentic true divided lite look. Interior wood in pine (standard), sapele, oak and cherry matching the interior wood species in either permanent or removable style ⅝" or ⅞" wide divided lite patterns only. Removable style not available in 1 ¼" and 1 ½" widths.
- Full surround removable wood grilles available in ⅝" or ⅞" wide classic double stepped profile matching window interior wood species in pine (standard), sapele, oak and cherry in a wide array of standard or custom divided lite patterns only. Grille frame utilizes a snap-in installation with concealed hardware.
- In-glass aluminum "GBG" (Grille Between the Glass) muntins are available in ⅝" flat profile or ⅞" contoured profile in all standard exterior cladding color finishes for dust free easy cleaning. Available in either divided lite or diamond patterns.
- Combo wood-aluminum: ⅝" flat profile or ⅞" contoured in-glass aluminum muntin with either permanently applied (see SDL) or removable wooden interior wood grille in pine (standard), sapele, oak and cherry.

ACCESSORIES

- A standard zero clearance mullion is used for factory mulling of windows without increasing the combined unit dimension of the windows mullied.
- Interior wooden mullion covers in pine (standard), sapele, oak and cherry are provided loose.
- 1 ¼" interior wooden jamb extension in pine are factory applied to the perimeter of the window and are available in custom sizes to provide an overall jamb depth up to 9".

THERMAL PERFORMANCE

Glass	U-Factor		R-Value		No Grids		Grids <1"		CRF
	No Grids	<1" Grids	No Grids	<1" Grids	SHGC	VT	SHGC	VT	
CARDINAL LoE ² -270	0.3100		3.226		0.31	0.57	0.28	0.50	56
CARDINAL LoE ² -270 + LoE-i89	0.2700		3.704		0.31	0.55	0.28	0.49	46

CARDINAL LoE²-270 = 3 mm LoE²-270 (position #2) / Argon / 3 mm Clear

CARDINAL LoE²-270 + LoE-i89 = 3 mm LoE²-270 (position #2) / Argon / 3 mm LoE-i89 (position #4)

STRUCTURAL PERFORMANCE

- Test specimen: 60.00" × 60.00" (1524 mm × 1524 mm)
- Air Infiltration: < .01 cfm/ft²
- Performance Class-Grade: CW-70