



SKC150

Aluminum Clad-Wood • Eclipse Premium Sash Replacement Kit • Jamb Liners Only

PRODUCT SPECIFICATIONS

FRAME

- Vinyl jambliners are pre-loaded with block and tackle balancers and are cut and notched to sill angle specified (zero to 14 degrees).
- Foam backed jambliners are reinforced with an extruded aluminum channel and are pre-drilled for installation screws and jamb adjuster. Snap-in caps are provided to cover all installation holes.
- Vinyl head plate is foam backed and includes weatherstripping and a ponderosa pine head plate.
- Vinyl sill profile is reinforced with an aluminum extrusion insert which allow the unitized frame to be securely fastened at the existing window sill.
- Vinyl jambliners, headplate, and sill profile are available in either white or beige.
- The vinyl frame system is designed for field assembly; optional factory assembly available.

SASH

- Exterior surfaces are covered with .019" thick roll-formed aluminum cladding.
- Sash parts are fitted to the extruded aluminum and are of kiln dried ponderosa pine, treated with a water repellent preservative to protect from rot and insects. Also available in sapele, oak and cherry.
- Sash joints are tenoned, glued and nailed from the interior.
- Silicone glazed from the interior for a positive water tight seal.
- Overall finish sash thickness: 1 7/16".
- Sash profile widths are: top rail (2 5/8" (standard); optional 1 3/4" available), stiles (1 3/4" (standard); optional 2 5/8" available), bottom rail (3 1/4" (standard); optional 2 5/8" and 4" available.)

EXTERIOR FINISH

- Standard color options are: White, Bronze, Earthtone, Beige, Black and Hunter Green and meet the physical test requirements of AAMA 2603. Custom colors available.
- Optional AAMA 2605 finish available.

INTERIOR FINISH

- Standard in unfinished natural wood in specified species (pine (standard), sapele, oak and cherry) which can be painted or stained.
- Available factory primed or prefinished white in pine (standard), sapele, oak and cherry. Contact Trimline dealer for custom color details.
- Interior features a concealed jambliner giving the appearance of a traditional wood window.

HARDWARE

- Hardware available in these following styles: Traditional, Restoration II and Eclipse.
- Traditional and Restoration II hardware - Sash lock and keeper are surface mounted cam action style. Recessed E-Z tilt sash release latches for top and bottom sash tilting. Dual lock/ lifts standard on units over 28" wide; triple locks standard on units over 50" wide. Sash lifts standard at bottom rail.
- Traditional style hardware is available in these finishes: White (Painted), Beige (Painted), Earthtone (Painted), Oil Rubbed Bronze (Plated), Polished Chrome (Plated), Satin Chrome (Plated), Antique Brass (Plated), Polished Brass (Plated) and Satin Nickel (Plated).
- Restoration II style hardware is available in these finishes: White (Painted), Beige (Painted), Earthtone (Painted), Oil Rubbed Bronze (Plated), Polished Chrome (Plated), Satin Chrome (Plated), Antique Brass (Plated), Polished Brass (Plated) and Satin Nickel (Plated).
- Eclipse style hardware is available in these finishes: White (Painted), Beige (Painted), Earthtone (Painted), Oil Rubbed Bronze (Plated), Polished Chrome (Plated), Satin Chrome (Plated), Antique Brass (Plated), Polished Brass (Plated) and Satin Nickel (Plated).
- The Ultra-Fit system includes jamb adjusters which are anchored in an aluminum channel reinforcement to provide jambliner adjustment to remove any bowing or hour-glassing.

BALANCES

- Concealed block and tackle system for smooth and effortless operation with locking cam action pivot shoes that never needs adjusting. AAMA 902-07 tested for over 28,000 cycles without failure.
- Class V Ultra-Lift® balances for units in which the sash weighs ≥ 45 lbs.

WEATHERSTRIPPING

- Head, meeting rails and bottom rail are weather sealed with Q-Lon® almond color compression seal foam; Fin-Seal® at the sill dam.
- Vertical stiles are sealed via Q-Lon® foam compression seal inserted into a flexible t-slot which is integral to the jambliner. Flexible T-slot assists the compression seal substantially in compensating for any “bowing” occurring during installation.

GLASS

- Standard clear $1\frac{1}{16}$ " thick insulating glass, consisting of “double strength” $\frac{1}{8}$ " (3 mm) annealed glass, $\frac{7}{16}$ " air space using Tremco's EnerEDGE® warm-edge, dual-seal silicone foam spacer (dark charcoal), hermetically sealed with hot melt butyl.
- Glass also available in these thicknesses: $\frac{3}{32}$ " (3.9 mm) with $\frac{3}{8}$ " air space, $\frac{3}{16}$ " (4.7 mm) with $\frac{5}{16}$ " air space and $\frac{7}{32}$ " (5.7 mm) with $\frac{1}{4}$ " air space.
- Other glazing options include CARDINAL LoE²-270 and with obscure, tempered, laminated, bronze or grey tint. Decorative glass also available. CARDINAL LoE²-270 + LoE-i89 is available only in annealed and tempered.

INSECT SCREENS

- Optional full screen of .019" thick roll-formed aluminum.
- Standard colors available: White, Bronze, Earthtone, Beige, Black and Hunter Green and meet the physical test requirements of AAMA 2603. Custom colors available.
- Charcoal fiberglass screen cloth (18" × 16" mesh) standard; optional screen mesh available in charcoal or aluminum color wire or Better View™ high transparency screening in charcoal fiberglass cloth only.

GRILLES

- Simulated Divided Lites (SDL) of .050" thick extruded aluminum in a classic putty glazed $\frac{5}{8}$ ", $\frac{7}{8}$ ", 1 $\frac{1}{4}$ " or 1 $\frac{1}{2}$ " muntin profile permanently applied to exterior of the insulated glass. Double faced tape is used to apply muntin to the glass which first is prepared with a saline type glass bonding and coupling agent before muntin is applied to help ensure lasting adhesion. An optional between the glass dark anodized bronze shadow bar is available for an authentic true divided lite look. Interior wood in pine (standard), sapele, oak and cherry matching the interior wood species in either permanent or removable style $\frac{5}{8}$ " or $\frac{7}{8}$ " wide divided lite patterns only. Removable style not available in 1 $\frac{1}{4}$ " and 1 $\frac{1}{2}$ " widths.
- Removable wood grilles available in $\frac{5}{8}$ " or $\frac{7}{8}$ " wide classic double stepped profile matching window interior wood species in pine (standard), sapele, oak and cherry in a wide array of standard or custom divided lite patterns only.
- In-glass aluminum “GBG” (Grille Between the Glass) muntins are available in $\frac{5}{8}$ " flat profile or $\frac{7}{8}$ " contoured profile in all standard exterior cladding color finishes for dust free easy cleaning. Available in either divided lite or diamond patterns.
- Combo wood-aluminum: $\frac{5}{8}$ " flat profile or $\frac{7}{8}$ " contoured in-glass aluminum muntin with either permanently applied (see SDL) or removable wooden interior wood grille in pine (standard), sapele, oak and cherry.